



Low Pressure Fittings and Tubing - Available components are elbows, tees, crosses, couplings, check valves and filters. Fittings and tubing used to complete flow system requirements.

Fittings

Elbows, Tees, Crosses, Couplings, and Bulkheads to 15,000 psi (1034 bar).

Autoclave's low pressure compression fitting line for use with 1/8" to 1/2" tubing rated to 15,000 psi (1034 bar).

▶ [Click here to view Product Information](#)



Mini Series Fittings

Elbows, Tees, Crosses, and, Couplings to 15,000 PSI (1034 bar).

Autoclave's mini series compression fitting line for use with 1/16" to 1/8" tubing rated to 15,000 psi (1034 bar).

▶ [Click here to view Product Information](#)



Tubing

Tubing from 1/16" to 1/2" outside diameter to 15,000 psi (1034 bar).

Seamless annealed stainless tubing from 1/16" to 1/2" outside diameter with various wall thicknesses, in lengths up to 27 feet, 24 feet average. Available in different materials.

▶ [Click here to view Product Information](#)



Check and Excess Flow Valves

O-ring and Ball Check Valves, and Excess Flow Valves to 15,000 psi (1034 bar).

Check valves to provide unidirectional flow with back flow shut-off for liquids or gases. Excess flow valves available in o-ring and ball design for surge protection.

▶ [Click here to view Product Information](#)



Line Filters

Dual-Disc and Cup Filters to 15,000 psi (1034 bar).

Dual-Disc filters used to trap larger particles in first filter to prevent clogging of smaller filter. Cup filters are used for high flow rates and provide maximum filter area.



▶ [Click here to view Product Information](#)
