



Medium Pressure Fittings and Tubing - Available components are elbows, tees, crosses, couplings, check valves and filters. Fittings and tubing used to complete flow system requirements.

Fittings

Elbows, Tees, Crosses, Couplings, and Bulkheads to 20,000 psi (1379 bar).

Autoclave's medium pressure coned and threaded fittings for use with 1/4" to 1" tubing rated to 20,000 psi (1379 bar).

▶ [Click here to view Product Information](#)



Tubing

Tubing from 1/4" to 1" outside diameter to 20,000 psi (1379 bar).

Seamless cold drawn stainless tubing from 1/4" to 1" outside diameter with various wall thicknesses, in lengths up to 27 feet, 24 feet average. Available in different materials.

▶ [Click here to view Product Information](#)



Nipples

Standard length Tubing Nipples to 20,000 psi (1379 bar).

Standard coned and threaded nipples 1/4" to 1" in lengths from 2.75" (69.9) to 12.0" (304.8)

▶ [Click here to view Product Information](#)



Check and Excess Flow Valves

O-ring and Ball Check Valves, and Excess Flow Valves to 20,000 psi (1379 bar).

Check valves to provide unidirectional flow with back flow shut-off for liquids of gases. Excess flow valves available in ball design for surge protection.

▶ [Click here to view Product Information](#)



Line Filters

Dual-Disc and Cup Filters to 20,000 psi (1379 bar).

Dual-Disc filters used to trap larger particles in first filter to prevent clogging of smaller filter. Cup filters are used for high flow rates and provide maximum filter area.

▶ [Click here to view Product Information](#)

Anti-Vibration Collet Gland Assembly

Series **KCBGLX Anti-Vibration Assemblies**

Anti-Vibration assemblies for medium pressure connections from 1/4" to 1" sizes. Used in extreme conditions of vibrations and/or shock in tubing systems, such as an unsupported line near a compressor.

▶ [Click here to view Product Information](#)

